



ABN 36 062 949 973
44/59-69 Halstead St South Hurstville NSW 2221

TEST CERTIFICATE

**Product Labelled as: "Play Bark" supplied by
"Scapeworks Australia"**

This is to certify that the product supplied by Scapeworks Australia, has been assessed according to the impact test procedure described in
Australian Standard: AS 4422:2016

Critical Fall Height: > 3.0m

Test Date	Product: Tested Wet and Dry	Critical Fall Height	Installation Depth #
24/11/2019	Play Bark	>3.0m	200mm

Recommended installation depth: **300mm**

Retest Date: October 2022

Reference: Archive sample held by Acousto-Scan 6161A

The Australian Standard AS4422:2016 details the usage of impact absorbing materials in children's playgrounds and defines relevant terms and conditions.

The Impact Attenuation Surface (IAS) shall have product labelling that uniquely identifies the product and its critical fall height. The product shall be labelled as Play Bark.

Loose particulate material should be installed to the depth of 300mm and should never be below 200 mm. Regular Maintenance is required to maintain this level.

This material shall also conform to the requirements of AS4685.0.2017. Maintenance shall conform to AS4685.0.2017.

Grant Humphreys
Laboratory Director
Date: 11/11/2019

Checked By

Date 12/11/2019